



EN

TACTICAL VEST «LORICA»



STORAGE CONDITIONS

Store in a dry and clean space.

MAINTENANCE

Easy to repair, pieces easily changeable.

COLOURS

Black; Green; Blue; Beige and Grey.

COMPOSITION

Fabric 100% Polyester; Nylon Straps resistance to traction up to 150kg; Velcro.



Manufacture and materials: 100% Made in Portugal

GENERAL CHARACTERISTICS

Usage: Designed for the Armed Forces. Made to carry soft armour protection up to level IIIA, anti-trauma inserts and hard armour plates of gradual protection up to level IV.

The design follows the recommendations detailed in the document NATO STANREC 2911.

- 2 pockets for soft armour protection and / or anti-trauma inserts (front and back).
- 4 pockets for hard armour plates (front, back and sides); the size of the pockets respects usual dimensions: 25cm * 30cm; 15cm * 15cm // 10"*12"; 6"*6").
- Integrated MOLLE / PALS System.
- Easy to put on and taken off with 1 hand; to be put on opened in one side.
- "Rescue" strap on the back (resistance up to 150kg).
- Lightweight (size M < 1Kg) and easy to carry / store.
- Minimalistic and discreet design.
- Velcro for ID panels front and back.
- Does not interfere with the use of a ballistic (hip) belt.

Number of pieces of the vest: 6

Additional elements colours (straps and Velcro): black.

C L E A N I N G
I N S T R U C T I O N S



BALLISTIC PROTECTION PANEL

100% *Made in Portugal*
Materials 100% *Made in EU*



Ballistic tests results:

2 panels of 26 * 29 cm
of about 0,950 kg

Test shot distance: 5m

Calibre .44 MAG SJHP Ref.4453 of Speer 15.6g (436 ± 9.1) m/s

Position	Angle	Velocity (m/s)	Valid Impact (Yes/No)	Perforation (Yes/No)	Trauma (mm)
1	0°	437.9	Yes	No	39.8
2	0°	435.6	Yes	No	38.4
3	0°	436.2	Yes	No	36.2
4	30°	435.4	Yes	No	29.9
5	45°	441.6	Yes	No	20.3

Calibre .357SIG TMJ Ref.4362 of Speer 8.1g a (448 ± 9.1) m/s

Position	Angle	Velocity (m/s)	Valid Impact (Yes/No)	Perforation (Yes/No)	Trauma (mm)
1	0°	460.7	Yes	No	26.8
2	0°	461.5	Yes	No	26.4
3	0°	457.8	Yes	No	28.3
4	45°	460.1	Yes	No	17.4
5	30°	458.5	Yes	No	26.4
6	0°	447.2	Yes	No	27.4

Test uncertainty: ± 1.0 m/s in the velocity measurement
and ± 1.13 mm in the trauma measurement

*Tested by the institute Aitex (www.aitex.es)

Cleaning Instructions: Clean with a damp cloth only

EUROPA VICTRIX

Document written in accordance with the Regulation
(EU) 2016/425 of the European Parliament and of the
Council of 9 March 2016.

STATUTORY SEAT: Rua Monte do Vale, n°525, 4465-699
Leça do Balio (Matosinhos), Portugal

VAT: PT514659785

For orders or any other question, do not
hesitate to contact us through email:
evictrix@europavictrix.com / evictrix@gmail.com

or through the contact form on our website:
europavictrix.com

On the website, you will find more information on the
other products of *Europa Victrix*.

Please, to get the updates about the company, follow us
on Facebook and Instagram:

Facebook: [/europavictrix](https://www.facebook.com/europavictrix)

Instagram: [@europa.victrix](https://www.instagram.com/europa.victrix)